EB-G7905U 7 7000 Im EPSON

Easy to set-up and with low maintenance requirements, this 7,000-lumens WUXGA installation projector boasts bright images, vivid colours and 4K-enhanced detail

Ideal for professional-looking presentations in a variety of large venues, the EB-G7905U creates images with rich, vivid colours thanks to Epson's 3LCD technology and equally high White and Colour Light Output. With flexible installation and low maintenance, this 4K enhanced projector offers a fit-andforget solution for scenarios in which only superior projections will do.

Superior image quality

Ensure superb quality and the best possible delivery of presentations with this powerful installation projector for large venues. Featuring Epson's own 3LCD technology and equally high White and Colour Light Output, WUXGA resolution images are vivid and bright, even in daylight with its 7,000 lumens brightness. For a next-level viewing experience, the projector features 4K enhancement, giving images exceptional sharpness, clarity and detail.

Easy positioning

Thanks to a new range of motorised lenses, including optional ultra-short throw (UST) lens, and both vertical and horizontal lens shift, the projector benefits from true 360° installation flexibility allowing it to be placed almost anywhere.

KEY FEATURES

- Superior picture quality 3LCD technology; superior white balance; better colour matching
- HD images with 4K enhancement Exceptional sharpness, clarity and detail for the real 4K effect
- Flexible 360° installation True flexibility without distortion or loss of brightness
- Lens memory function Stores projector settings such as image position, focus and zoom
- Portrait projection mode Switch mode without having to change the lamp







IDBaseT





PRODUCT SPECIFICATIONS

TECHNOLOGY Projection System	3LCD Technology	
LCD Panel	0.76 inch with C2 Fine	
IMAGE		
Colour Light Output	7.000 lumen-5.600 lumen (economy) In accordance with IDMS15.4	
White Light Output	7.000 lumen - 5.600 lumen (economy) In accordance with ISO 21118:2012	
Portrait Colour Light Output	5.600 lm	
Portrait White Light Output	5.600 lm	
Resolution	WUXGA, 1920 x 1200, 16:10	
High Definition	4K enhancement	
Aspect Ratio	16:10	
Contrast Ratio	50.000 : 1	
Native Contrast	2.000 : 1	
Lamp	400 W, 3.000 h durability, 4.000 h durability (economy mode)	
Lamp (portrait mode)	400 W, 2.000 Hours Durability	
Keystone Correction	Manual vertical: \pm 45 °, Manual horizontal \pm 30 °	
Colour Reproduction	Upto 1.07 billion colours	
Colour Processing	10 Bits	
OPTION		
Projection Ratio	1,44 - 2,33:1	
Zoom	Motorized, Factor: 1 - 1,6	
Lens Shift	Motorized - Vertical ± 67 %, horizontal ± 30 %	
Lens position memory	10 positions	
Projection Size	50 inches - 300 inches	
Projection Lens F Number	1,7 - 2,3	
Focus	Motorized	
Projection Distance Wide	1,5 m - 9,4 m (50 inch screen)	
Projection Distance Tele	2,5 m - 15,1 m (50 inch screen)	
Focal Distance	24 mm - 38,2 mm	
CONNECTIVITY		
Interfaces	USB 2.0 Type A, USB 2.0 Type B (Service Only), RS-232C, Ethernet interface (100 Base-TX /	
	10 Base-T), Wireless LAN IEEE 802.11a/b/g/n (optional), VGA in, VGA out, DVI in, BNC in,	
	HDBaseT, Stereo mini jack audio out, Stereo mini jack audio in (3x), HDMI (HDCP 2.2)	
GENERAL		
Energy Use	572 W, 477 W (economy), 0,3 W (standby)	
Supply Voltage	AC 100 V - 240 V,50 Hz - 60 Hz	
Product dimensions	525 x 472 x 189 mm (Width x Depth x Height)	
Product weight	12,7 kg	
Noise Level	Normal: 39 dB (A) - Economy: 31 dB (A) (4K enhancement OFF)	
Colour	Black	
ADVANCED FEATURES	Kanalantan kale Oratari mani kale Provinsi di di	
Security	Kensington lock, Control panel lock, Password protection	
Features	4K enhancement, Built-in speaker, Document Camera Compatible, Lens position memory	
	O'REAL DIRECTOR DIO NON MARKED 1	
Video Colour Modes	Cinema, Dynamic, sRGB, DICOM SIM, Multi Projection	
	Cinema, Dynamic, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4	
Video Colour Modes		
Video Colour Modes Projector control		

EB-G7905U

WHAT'S IN THE BOX

- Cable cover
- Computer cable
- Lens cap
- Remote control incl. batteries
- User's Manual Set
- Power cable



OPTIONAL ACCESSORIES

- Air Filter ELPAF30
 V13H134A30
- Lamp ELPLP93 EB-G7000 series V13H010L93
- Ceiling Mount ELPMB47 Low EB-G7000/L1000 V12H802010
- Ceiling Mount ELPMB48 High EB-G7000/L1000 V12H803010
- 3D Polarizer ELPPL01 V12H618A01
- Adapter ELPAP10 Wireless LAN b/g/n V12H731P01
- Ceiling Mount (White) ELPMB22 V12H003B22
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14

OPTIONAL LENSES

- Lens ELPLU04 G7000 & L1000 Series ST off axis 2 V12H004U04
- Lens ELPLU03 G7000 & L1000 Series ST off axis 1 V12H004U03
- Lens ELPLW05 G7000 & L1000 Series wide zoom 1 V12H004W05
- Lens ELPLM08 Mid throw 1 G7000/L1000 series V12H004M08
- Lens ELPLL08 Long throw G7000/L1000 series V12H004L08
- Lens ELPLM10 Mid throw 3 G7000/L1000 series V12H004M0A
- Lens ELPLM11 Mid throw 4 G7000/L1000 series V12H004M0B
- Lens ELPLM09 Mid throw 2 G7000/L1000 series V12H004M09

LOGISTICS INFORMATION

ѕки	V11H749140
EAN code	8715946612133
Country of Origin	China

EB-G7905U

